

[www.lewitt-audio.com](http://www.lewitt-audio.com)



PUT  
MORE  
**BOOM**  
IN  
YOUR  
**CHA.**

DTP 340 REX

SOUNDS LIKE  **LEWITT**

Thank you that you have opted for a LEWITT product. In this operating manual you will learn more about your LEWITT microphone, its handling and its proper usage.

With its DTP series, LEWITT introduces a complete family of cutting-edge, high-performance wired dynamic microphones designed specifically for drums, percussion and bass instruments. On stage as well as in studio settings, these high quality mics – spear-headed by our masterpiece, the dual-element cardioid DTP 640 REX optimized for kick drum applications – stand out thanks to their sonic accuracy. Minimally affected by varying load impedance and designed to effectively reject off-axis sound, all models of the DTP series deliver unparalleled, memorable sound that will turn heads in any audience.

Uniform cardioids and super-cardioid patterns allow for high gain before feedback and a hardened steel mesh grille effectively resists wear and abuse, making DTP microphones and drum sets the ultimate choice for touring professionals.

From professional drummers to discerning beat aficionados, LEWITT's DTP series lets music lovers and performers alike discover a fine-tuned, punchy sound.

LEWITT wishes you a lot of fun and success with this product!



The entry-level DTP 340 REX and its upscale "big brother", the DTP 640 REX, make beat aficionados' hearts beat faster. Designed specifically for miking bass instruments and featuring a powerful dynamic capsule and a cardioid pattern, the DTP 340 REX exhibits superb response, delivering fine-tuned sound onstage and in the studio.



## Features

- Perfectly suited for bass instrument and percussion applications
- Cardioid pickup pattern ensures high gain before feedback and superior off-axis sound rejection
- Gold-plated 3-pin XLR output connector
- Durable hexagonal steel-mesh grille and solid die-cast body
- Integrated microphone stand and compact design for convenient positioning
- Comes in a cardboard box with foam layers; DTP 40 Lb leather bag included


## Top applications

- Bass instruments
- Live applications
- Recording

## Tech graph



## Dimension



## Tech data

- Acoustical operating principle: dynamic, moving coil
- Directional pattern: cardioid
- Frequency range: 20 ... 16,000 Hz
- Sensitivity: 2.5 mV / Pa (-52 dBV)
- Rated impedance: < 500 ohms
- Connector: gold plated 3-pin XLR
- Dimension: 71 dia. x 158 mm  
2.8 dia. x 6.2 inch
- Net weight: 740 g  
26.1 oz.

## Accessories



DTP 40 Lb



### Cautions

- The capsule is a sensitive, high precision component. Make sure you do not drop it from high heights and avoid strong mechanical stress and force.
- To ensure high sensitivity and best sound reproduction of the microphone, avoid exposing it to moisture, dust or extreme temperatures.
- Keep this product out of the reach of children.
- Do not use force on the switch or cable of the microphone.
- When disconnecting the microphone cable, grasp the connector and do not pull the cable.
- Do not attempt to modify or fix it. Contact qualified service personnel in case any service is needed. Please do not disassemble or modify the microphone for any reasons as this will void users warranty.
- The casing of the microphone can be cleaned easily using a wet cloth, never use alcohol or another solvent for cleaning. If necessary the foam wind stopper can be washed with soap water. Please wait till it is dry before using it again.
- Also please refer to the owner's manual of the component to be connected to the microphone.



### Warranty

All products manufactured by LEWITT GmbH feature a limited two-year warranty. This two-year warranty is specific to the date of purchase as shown on your purchase receipt.

LEWITT GmbH shall satisfy the warranty obligations by remedying any material or manufacturing faults free of charge at LEWITT's discretion either by repair or by exchanging individual parts or the entire appliance. Any defective parts removed from a product during the course of a warranty claim shall become the property of LEWITT GmbH.

While under warranty period, defective products may be returned to the authorized LEWITT dealer together with original proof of purchase. To avoid any damages in transit, please use the original packaging if available. Please do not send your product to LEWITT GmbH directly as it will not be serviced. Freight charges have to be covered by the owner of the product.

Certain products manufactured by LEWITT GmbH feature a limited five-year warranty. For this five-year warranty the same conditions as listed for the two-year warranty are applicable.

For further information please visit [www.lewitt-audio.com](http://www.lewitt-audio.com) or check your warranty card.



LEWITT GmbH declares under its sole responsibility that DTP 340 REX complies with the European directive 2004/108/EC. The product has been tested according to harmonized European standards:

EN 55013:2001+A1:2003+A2:2006

EN 55020:2007

EN 61000-3-2:2006

EN 61000-3-3:1995+A1:2001+A2:2005

Product testing was carried out by TIMCO Engineering Inc., notified body number 1177.

LEWITT GmbH hereby declares under its sole responsibility that DTP 340 REX has been tested and conforms to the following FCC and ANSI standards:

FCC Part 15:2008 Section 15.109

ANSI C63.4:2003

Product testing was carried out by INTERTEK Testing Services Shenzhen Ltd.



WEEE note: Electronic waste has to be collected separately. Please bring this device to a local recycling center at the end of its life time.

Manufacturers signature:

Date: 18th November 2010

Place: Vienna, AUSTRIA

DI Roman Perschon

CEO – Lewitt GmbH

Declaration of conformity can be downloaded at [www.lewitt-audio.com](http://www.lewitt-audio.com) or obtained from [info@lewitt-audio.com](mailto:info@lewitt-audio.com).



Mooslackengasse 17  
1190 Vienna  
AUSTRIA  
[info@lewitt-audio.com](mailto:info@lewitt-audio.com)



**LEWITT**