





The RØDE M1 dynamic microphone was designed to be the Roadie's best friend. Its rock solid die-cast body and sturdy dynamic capsule ensure the M1 can take all the abuse you can throw at it without showing signs of age or neglect.

RØDE's attention to detail has resulted in a microphones that will continue to offer high quality performance, day after day.

Features

- Live dynamic vocal microphone
- High output dynamic capsule
- Gold plated XLR connectors .
- Balanced, low impedance output •
- Internal pop-filter to reduce plosives •
- Feedback rejecting pick up pattern •
- Heavy duty metal body .
- Low handling noise •


- Designed and manufactured in Australia
- Full 10 year warranty*


Specifications

Acoustic Principle	Dynamic
Frequency Range	75Hz ~ 18,000Hz
Nominal Impedence	320Ω
Net Weight	360g (0.79lb)
Directional Pattern	Cardioid
Sensitivity	-56dB ±2dB re 1V/Pa (1.6mV @ 94 dB SPL) @ 1kHz
Dimensions	Length - 171mm (6.73") Diameter - 51.5mm (2.03")
Shipping Weight	700g (1.54lb)
Output Connection	3 pin XLR, balanced output between Pin 2 (+), Pin 3 (-) and Pin 1 (ground)

Included Accessories

- RM1 stand mount
- ZP1 zip pouch





www.rodemic.com

Australia 107 Carnarvon st, Silverwater NSW 2128 Australia Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA PO Box 4189 Santa Barbara CA 93140 USA Ph: +1 805 566 7777 Fx: +1 805 566 0071