

NTR

Active Ribbon Microphone

AUSTRALIA
107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA
PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664




Features

- Highly sensitive 1.8 micron ribbon element
- Bi-Directional Polar Pattern
- Internal Shock Mounting System
- Custom designed and manufactured transformer
- Heavy-duty matte black finish
- Ribbon-securing travel screw supplied
- Designed and manufactured in Australia
- One free ribbon replacement during warranty period
- Free 10 year extended warranty when you register online at www.rodemicrophones.com/warranty

Specifications

Acoustic Principle	Velocity transducer
Active Electronics	Step-up Transformer and signal balanced preamp stage
Directional Pattern	Figure 8
Frequency Range	20Hz ~20000 Hz
Output Impedance	200 \pm
Signal to noise Ratio	79.3dBa
Equivalent Noise	15 dbA SPL (as per IEC651)
Maximum SPL	130dB SPL
Maximum Output	8dBu (@ 1KHz, 1% THD into 1K \pm load)
Sensitivity	-30.5 dB re 1V/Pa (30mV @ 94dB SPL) \pm 2dB @ 1kHz
Dynamic Range	115dB SPL
Power Requirements	P48
Output Connection	3 Pin XLR - Balanced output between Pin 2 (+) Pin 3 (-) and Pin 1 (ground)
Weight	1047g

Polar Pattern



Frequency Response

