



ROYER R-122

Active Ribbon-Velocity Studio Microphone

The R-122 is a compact, monaural, phantom powered ribbon microphone - the first ribbon microphone of its kind. Sonically similar to our R-121, the R-122 exhibits a flat frequency response and a well balanced, panoramic soundfield, but it is 13 dB more sensitive, its transient response is faster and its electronics provide an optimum load to the ribbon element at all times. Like the R-121, its ability to withstand high SPL's makes it ideal for applications that were previously considered off limits to ribbon microphones.

The R-122's active electronics produce an output comparable to studio condenser microphones and provide an optimum impedance to the ribbon element, preventing overdamping of the ribbon element and assuring consistent microphone performance. The high gain and low output impedance of the R-122 allow it to operate with any microphone preamplifier with phantom power, including those of nominal gain and input impedance characteristics. It is also well suited for use with long cable runs, which can be helpful in live situations.

The R-122 utilizes a low mass, 2.5-micron, pure (99.99%) aluminum ribbon element. The R-122's unique, patented offset-ribbon transducer assembly incorporates rare earth Neodymium magnets in a specially designed flux frame, which forms a powerful magnetic field while reducing unwanted stray magnetic radiation. The smooth frequency response and phase linearity of the R-122, coupled with its sophisticated active electronics system, enable the R-122 to deliver a consistent natural acoustic performance with stunning realism. Frequency response is excellent regardless of the angle of sound striking the ribbon, and off-axis coloration is negligible.

The R-122's offset-ribbon design positions the ribbon element toward the front of the microphone body, which allows for high SPL handling on the front (logo) side and the option of a slightly brighter response when recording lower SPL sound sources on the back side (3 feet and closer; phase reversed in this position).

R-122 FEATURES

- Active electronics provide high output capability, optimal impedance to the ribbon element, extremely low self-noise and low output impedance
- Operates on standard 48-volt phantom power
- High SPL capabilities for electric guitar and percussion instruments
- Absence of high frequency peaks, "ringing" and phase shifts
- Ribbon element unaffected by impedance/load, heat or humidity
- Equal sensitivity from front and back of ribbon element
- Very low magnetic leakage
- Gold plated XLR contacts

RECOMMENDED APPLICATIONS

- Close and distant miking
- Electric and acoustic guitar
- Vocals, commercial broadcast, voiceover
- Brass, horn sections
- Drum overheads, kick drum (see manual for position), room miking
- Percussion instruments
- Strings - solo & sections
- Acoustic piano, harp
- Live events - recording and sound reinforcement



Actual size

ROYER R-122



Technical Specifications



Acoustic Operating Principle	Electrodynamic pressure gradient with active electronics.
Polar Pattern	Figure-8
Generating Element	2.5-micron aluminum ribbon
Magnets	Rare Earth Neodymium
Frequency Response	30 - 15,000 Hz ± 3 dB
Sensitivity	-37 dB (re. 1v/pa ± 2 dB)
Self-Noise	< 18 dB
Output Impedance	200 Ohms, balanced
Output Connector	Male XLR 3-pin (Pin 2 Hot)
Rated Load Impedance	1K-Ohm minimum
Maximum SPL	135 dB @ 30 Hz
Power Requirements	48-Volt Phantom Only
Supply Current	4 mA
Dimensions	206mm L X 25mm W (8 1/8" L X 1" W)
Weight	309 grams (10.9 oz)
Finish	Burnished Satin Nickel / Matte Black Chrome (optional)
Accessories	Protective wood case, mic sock
Optional Accessories	Wind screen, shock mount
Microphone Warranty	Lifetime to original owner (repair or replace at Royer's option)
Ribbon Element Warranty	One Year

Matched pairs are available at extra charge

Frequency Response and Polar Pattern



Patent Number: 6,434,252

Royer Labs
www.royerlabs.com

2711 Empire Ave, Burbank, CA 91504
 Tel. (818) 847-0121 Fax (818) 847-0122

COPYRIGHT ROYER LABS 2006
 All specifications subject to
 change without notice